科目:作業系統 (Operating System) 第一頁 共四頁 (page 1 of 4)

1.(35%)There are two example program, the following one(figure 5.9, 5.10) uses semaphore to implement it.(p240, Fig 6.10/6.11 8th edition,p269, Fig 6.9/6.10 9th edition)

```
int n;
semaphore mutex = 1;
semaphore empty = n;
semaphore full = 0
do {
    ...
    /* produce an item in next_produced */
    ...
    wait(empty);
    wait(mutex);
    ...
    /* add next_produced to the buffer */
    ...
    signal(mutex);
    signal(full);
} while (true);
```

Figure 5.9 The structure of the producer process.

```
do {
   wait(full);
   wait(mutex);
    ...
   /* remove an item from buffer to next_consumed */
    ...
   signal(mutex);
   signal(empty);
   ...
   /* consume the item in next_consumed */
    ...
} while (true);
```



In another consumer-producer example program figure 3.13 and 3.14, a ring buffer queue is used to store the produced item that will be take off by the consumer later.

背面還有 Please Turn Over

科目:作業系統 (Operating System) 第二頁 共四頁 (page 2 of 4)

```
#define BUFFER_SIZE 10
          typedef struct {
              . .
          }item;
          item buffer[BUFFER_SIZE];
          int in = 0;
          int out = 0;
while (true) {
     /* produce an item in next_produced */
     while (((in + 1) % BUFFER_SIZE) == out)
       ; /* do nothing */
     buffer[in] = next_produced;
     in = (in + 1) % BUFFER_SIZE;
}
  Figure 3.13 The producer process using shared memory.
        item next_consumed;
        while (true) {
             while (in == out)
                ; /* do nothing */
             next_consumed = buffer[out];
```

out = (out + 1) % BUFFER_SIZE;
/* consume the item in next_consumed */

Figure 3.14 The consumer process using shared memory.

1-a.(10%) Assume multiprocessors will be used in these two examples. Without using semaphore functions (fig 3.13 3.14), Explain why more than one producer processes, produce-1, producer-2 ...producer-i programs could not be correctly executed concurrently?

}

1-b.(10%) Assume only one producer and only one consumer can be assigned to execute concurrently. Show that even in more than two processors(multi-core) parallel processing system, without using any semaphore operation functions (fig 3.13 3.14) the result is still correct?

<u>科目:作業系統(Operating System) 第三頁 共四頁 (page 3 of 4)</u>

1-c. (10%)The critical section problem is caused by the race condition that the timer interrupt will break the updating statement of list queue pointer into non-atomic operation. If there are only one producer and only one consumer program in running, Please indicate what is (or none) of the critical region in 3.13 and 3.14 example program? 1-d.(5%) If kernel monitor(R.C.A. Hoare Monitor) approach is adopted to support producer and consumer program. Any processes that can not call consumer or producer function in monitor simultaneously. That means the monitor restricts the parallel processing of these two functions. What is your suggestion to use 3.13/3.14 or 5.9/5.10 algorithm in monitor to support multiprocessor parallel processing? Why?

2-a.(5%)Show how to implement the mutual exclusion operations in multiprocessor shared memory environments using the swap() instruction.

2-b.(10%)The two process mutual exclusive lock algorithm(Petersons algorithm) in current multi-core architecture, the hardware processors and/or software compilers may reorder read and write operations that have no dependencies. The reordering of instructions may render inconsistent or unexpected results. That cause this algorithm will not be correct. For queue/list pointer update operation may cause data race on a single variable, Please considering the multi-processors and shared memory environments, using the compare and swap () operation and atomic variables to implement the atomic interger sequence function: increment(&sequence) [Intel X86 using a special prefix instruction to assure atomic function]

3. (15 %) Are the following statements true or false? For each statement, you will get 3 points for correct answer, zero point for blank, or -2 point for incorrect answer.

- (a) The subnet mask for the subnet 200.23.16.0/23 is 255.255.255.0.
- (b) The subnet 200.23.16.0/23 could accommodate up to 256 hosts.
- (c) Domain Name Service (DNS) can be used to acquire IP addresses.
- (d) Address Resolution Protocol (ARP) can be used to acquire IP addresses.
- (e) Network Address Translation (NAT) is used to map MAC addresses to IP addresses.

4. (20 %) Suppose that a disk drive has 5000 cylinders, numbered 0 to 4999. The drive is currently serving a request at cylinder 134, and the previous request was at cylinder 125. The queue of pending requests, in FIFO order, is 86, 1470, 913, 3774, 948, 4509, 1022, 2750, 130. Starting from the current head position, what is the total distance (in cylinders) that the disk arm moves to satisfy all the pending requests, for SSTF and SCAN disk scheduling algorithms?

背面還有 Please Turn Over

<u>科目:作業系統(Operating System)</u> 第四頁 共四頁 (page 4 of 4)

5. (15 %) Suppose that a scheduling algorithm (at the level of short-term CPU scheduling) favors those processes that have used the least processor time in the recent past.

(a) (8 %) Will this scheduling algorithm favor CPU-bound processes or I/O-bound processes? Why?

(b) (7%) Please discuss if the starvation situation will permanently occur in this scheduling algorithm?